



Serenity Choice™ Sleep

The high-end hearing protection
from the hearing care specialist



A Sonova brand

PHONAK
life is on



A moderate snorer reaches 50–60 dB whilst severe snoring can hit 90 dB. To put that in perspective; a car horn is around 90 dB! Serenity Choice™ Sleep reduces the sound level by 24 dB, eliminating or reducing sound to a non-intrusive level.

Serenity Choice™ Sleep is designed to allow air to enter the ear. This has two advantages over competing products;

- Limits or stops that uncomfortable 'hot' irritation feeling in your ear.
- Helps reduce the feeling of 'hearing your pulse' caused by restricting blood flow in the ear, especially noticeable when laying on your side.

Sleeping with ear tips will take a little getting used to, as it can sound unnaturally quiet for the first night. After that you'll wonder why you didn't use them earlier.

Product specific benefits

- A perfect fit is guaranteed: Small, medium and large ear tips in package, extra large size available on request.
- Hygienic: Acoustic filters are fitted with advanced mesh technology. They ensure that your ears remain well ventilated at all times.
- Hypoallergenic: ear tips are made from medical grade TPE.
- Value for money: ear tips can be used multiple times.
- Natural: Natural hearing is preserved, which facilitates situational awareness.

24 | 16
SNR | NRR

Sound Reduction:

Ventilation of the Ear:

Product applications

- Reduces the effect of a partner snoring
- Noisy hotels – reduces noise from lifts, revellers, kitchen noise, etc.
- Street noise – reduction in car noise, refuse collection, revellers, etc
- Deeper rest

In the box

- 2 ear tips of each size S, M, L
- Two acoustic filters 24 dB
- Aluminum key-ring carrying case
- Multilingual manual

Certification Data Serenity Choice™ Sleep (KI 25)

CE	125 (Hz)	250 (Hz)	500 (Hz)	1 (kHz)	2 (kHz)	4 (kHz)	8 (kHz)	H	M	L	SNR
Mean attenuation (dB)	23.2	22.3	22.7	24.8	30.8	22.5	36.7				
Standard deviation (dB)	3.0	2.6	2.6	3.6	3.3	2.9	3.5	23	22	21	24
APV 95% (dB)	20.2	19.7	20.1	21.2	27.5	19.6	33.2				

ANSI	125 (Hz)	250 (Hz)	500 (Hz)	1 (kHz)	2 (kHz)	3.15 (kHz)	4 (kHz)	6.3 (kHz)	8 (kHz)	NRR
Mean attenuation (dB)	22.1	20.7	20.5	24.3	31.1	31.6	21.8	22.7	33.7	
Standard deviation (dB)	3.0	2.8	3.6	3.8	4.0	5.1	3.2	3.4	4.1	16
APV 98% (dB)	18.1	15.1	13.3	16.7	23.1	-	18.4	-	20.7	

